



NOTE:

1) DIMENSIONS INCHES [mm]

- 2) UNIT HEIGHTS MAY VARY BY MODEL
 - UNIT HEIGHT; SHORT COVER W/O VISUAL INDICATOR = 3.26" [82.8 mm]
COVER REMOVAL CLEARANCE REQUIRED = 1.50" [38.1 mm]
 - UNIT HEIGHT; SHORT COVER W/ VISUAL INDICATOR = 3.96" [100.6 mm]
COVER REMOVAL CLEARANCE REQUIRED = 1.50" [38.1 mm]
 - UNIT HEIGHT; TALL COVER W/ VISUAL INDICATOR = 6.38" [162.1 mm]
COVER REMOVAL CLEARANCE REQUIRED = 3.32" [84.3 mm]

3) CONSULT FACTORY FOR COVER SIZE ON SPECIFIC MODELS.

4) CONSULT FACTORY FOR CONDUIT / CONNECTOR SIZE AND QUANTITY ON SPECIFIC MODELS.

5) CONSULT FACTORY FOR MOUNTING HOLE PATTERNS ON SPECIFIC MOUNTING SET APPLICATION. MOUNTING HARDWARE REQUIRED AND SOLD SEPERATELY.

REVISIONS	A	9837	06/24/14	JL	CONFIDENTIAL THIS DRAWING AND ALL INFORMATION CONTAINED HEREIN IS THE PROPERTY OF AND IS SUBJECT TO CHANGE BY STONEL. DRAWING IS NOT TO BE REPRODUCED OR REVEALED TO ANY OTHER PARTY UNLESS AUTHORIZED BY STONEL.	 METSO AUTOMATION, FERGUS FALLS, MN U.S.A.		
	REVISION	ECO	DATE	BY				
	TOLERANCES (UNLESS OTHERWISE SPECIFIED): X.XXX ± .005 ANGLES ± 0° 30' X.XX ± .010 FINISH f 125 RMS X/X ± .015							
					500134	A		